

## DESIGI RIME

A Safe Fleet Brand

**CHEVROLET CITY EXPRESS** 

Complete everyday tasks with world-class designs

Transport more tools, keep productivity high and lower the risk of injuries and worker compensation claims by installing the right ladder-rack solution on your Chevrolet City Express.

Prime Design's ergonomic, patented and award-winning solutions have helped business owners around the world eliminate or reduce the costs, stress and business pressures caused by work-related injuries.





of your City Express with an ErgoRack.





Easy to use - deploys with only 2 fingers.



Maintain vehicle warranty and resale value with no holes to drill.



Eliminates slip and fall hazards from climbing on bumper or tire.



Control ladder deployment with adjustable hydraulic cylinder.



Improve productivity – Deploy or stow in less than 20 seconds.



Winner of ergonomic awards in USA, France, Germany and Australia.



Search term "Chevrolet City Express ErgoRack" to find more information.





Images shown are for illustrative purposes only. Actual colors, finishes, and/or vehicle mounting hardware may vary depending on the vehicle and product model selected









MODELS	VEHICLE WHEELBASE	VEHICLE HEIGHT	STREET SIDE FEATURE	CURB SIDE FEATURE	WEIGHT
VBB-CE	115 IN	Standard	End Stop	End Stop	27 lbs
VBC-CE VCB-CE	115 IN	Standard	End Stop Clamp	Clamp End Stop	42 lbs
VBR-CE VRB-CE	115 IN	Standard	End Stop Rotation	Rotation End Stop	69 lbs
VCC-CE	115 IN	Standard	Clamp	Clamp	57 lbs
VCR-CE VRC-CE	115 IN	Standard	Clamp Rotation	Rotation Clamp	84 lbs
VRR-CE	115 IN	Standard	Rotation	Rotation	112 lbs

## Notes:

Crossbars can be spaced at five or six feet.

Contact Prime Design customer service for application specific questions.

Check the vehicle manufacturer's recommendation for roof capacity weight limits.

A wide range of accessories are available including conduit carriers, lighting mounts, and more.

Van Crossbar	<b>Spacing</b>	and Ladd	er Size Guide

CROSSBAR SPACING	STEP LADDER SIZE	EXTENSION LADDER SIZE					
5 ft Spacing	8 – 10 ft.	16 – 24 ft.					
6 ft Spacing	8 – 12 ft.†	16 – 28 ft.					
<sup>†</sup> 12 ft. step ladders may require an extended upper add-on component.							

ML-7.2-4053 / Rev D / 05-30-2019