## **ErgoRack**



A Safe Fleet Brand

### For Ford Transit Connect





### Easy to use

Deploys with only 2 fingers.



### Improve productivity

Deploy or stow in less than 20 seconds.



### **Enhance Safety**

Eliminates slip and fall hazards from climbing on bumper or tire.



### No Drill Installation

Maintain vehicle warranty and resale value with no holes to drill.



# **ErgoRack**

## PRIME DESIGN

A Safe Fleet Brand

## For Ford Transit Connect



VCC-TC

Dual Clamp



VRR-TC

Dual Rotation



Clamp / Rotation with 3rd crossbar

VCR3-TC

Models	Vehicle Wheelbase	Vehicle Height	Street side Feature	Curb side Feature	Weight
VBB-TC	105 IN (Short) or 121 IN (Long)	72 IN	End Stop	End Stop	28 lbs
VBC-TC VCB-TC	105 IN (Short) or 121 IN (Long)	72 IN	End Stop Clamp	Clamp End Stop	43 lbs
VBR-TC VRB-TC	105 IN (Short) or 121 IN (Long)	72 IN	End Stop Rotation	Rotation End Stop	70 lbs
VCC-TC	105 IN (Short) or 121 IN (Long)	72 IN	Clamp	Clamp	58 lbs
VCR-TC VRC-TC	105 IN (Short) or 121 IN (Long)	72 IN	Clamp Rotation	Rotation Clamp	85 lbs
VRR-TC	105 IN (Short) or 121 IN (Long)	72 IN	Rotation	Rotation	113 lbs

#### Notes

Crossbars can be spaced at five or six feet.

Contact Prime Design customer service for application specific questions.

Check the vehicle manufacturer's recommendation for roof capacity weight limits.

A wide range of accessories are available including conduit carriers, lighting mounts, and more.

#### Van Crossbar Spacing and Ladder Size Guide

Crossbar Spacing	Step Ladder Size	Extension Ladder Size
5 ft Spacing	8 – 10 ft.	16 – 24 ft.
6 ft Spacing	8 – 12 ft.†	16 – 28 ft.

†12 ft. step ladders may require an extended upper add-on component.



