

ErgoRack

For Ram ProMaster

PRIME DESIGN™

A Safe Fleet Brand



PRIME TIME
Quick Ship Product



Maximize the safety and carrying capacity of your Ram ProMaster with an ErgoRack.



Easy to use

Deploys with only 2 fingers.



Improve productivity

Deploy or stow in less than 20 seconds.



Enhance Safety

Eliminates slip and fall hazards from climbing on bumper or tire.



No Drill Installation

Maintain vehicle warranty and resale value with no holes to drill.

SAFE  FLEET
Driving Safety Forward™

ErgoRack

For Ram ProMaster

PRIME DESIGN™

A Safe Fleet Brand



HBB-PM

Base Rack



HRR-PM

Dual Rotation



HRR3-PM

Dual Rotation with 3rd crossbar

Models	Vehicle Wheelbase	Vehicle Height	Street side Feature	Curb side Feature	Weight
HBB-PM	118 IN, 136 IN, 159 IN, or 159 IN Ext.	90 IN (Low) or 101 IN (High)	End Stop	End Stop	45 lbs
HBR-E-PM HRB-E-PM	118 IN, 136 IN, 159 IN, or 159 IN Ext.	90 IN (Low) or 101 IN (High)	End Stop	Rotation	100 lbs
HRR-E-PM	118 IN, 136 IN, 159 IN, or 159 IN Ext.	90 IN (Low) or 101 IN (High)	Rotation	Rotation	155 lbs
HRR3-E-PM*	118 IN, 136 IN, 159 IN, or 159 IN Ext.	90 IN (Low) or 101 IN (High)	Rotation	Rotation	166 lbs

*Three crossbar rack

Notes:

Crossbar spacing and the vehicle's wheelbase length will dictate the ladders that can be carried. Crossbars can be spaced at six, seven, or eight feet.

A 3rd crossbar can be spaced four, five, six, or seven feet.

If carrying a long extension ladder and a short step ladder, a three crossbar rack is suggested. Contact Prime Design customer service for application specific questions.

Check the vehicle manufacturer's recommendation for roof capacity weight limits.

A wide range of accessories are available including conduit carriers, light holders, and more.

Van Crossbar Spacing and Ladder Size Guide

Crossbar Spacing	Step Ladder Size	Extension Ladder Size
4 ft Spacing	6 – 8 ft.	16 – 20 ft.
5 ft Spacing	8 – 10 ft.	16 – 24 ft.
6 ft Spacing	8 – 12 ft. [†]	16 – 28 ft.
7 ft Spacing	10 – 12 ft. [†]	20 – 32 ft.
8 ft Spacing	10 – 12 ft. [†]	20 – 36 ft.

[†]12 ft. step ladders may require an extended upper add-on component.



ML-7.2-4060 / Rev D / 2-26-2020

Copyright ©2020 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.

1.877.630.7366
safefleet.net

