

ErgoRack®

For Chevrolet City Express

PRIME DESIGN™

ErgoRack eliminates the strain from unloading and stowing heavy ladders onto work vehicles.

This regularly performed operation can get cumbersome, especially when factoring in ladder weights, ladder lengths, operator body types, and vehicle heights. Quite often, a worker takes the unnecessary risk of climbing on a vehicle's tire or bumper to complete this task.



■ Easy to use

Make unloading and stowing heavy ladders from a vehicle's roof easy and with less strain.

■ Enhance Safety

Ladder deployed to operator versus climbing on bumper or tire which eliminates slip and fall hazards.


■ Improve productivity

Deploy or stow in less than 20 seconds.

■ No Drill Installation

Maintain vehicle warranty and resale value with no holes to drill.

Features:



Ergonomically Designed



Hydraulically Dampened Descent



Auto Clamped



Easy Compatibility



Built-In Security



Built for Efficiency



Customizable Configurations

TO LEARN MORE VISIT: PRIMEDESIGN.NET/PRODUCTS/ERGORACK/ OR SCAN THE QR CODE





CC-CE-62-M
Dual Clamp



CR-CE-62-M
Clamp / Rotation



RR-CE-62-M
Dual Rotation

Models	Vehicle Wheelbase	Vehicle Height	Street Side Feature	Curb Side Feature	Weight
BB-CE-62-M	115 IN	Standard	End Stop	End Stop	27 lbs.
BC-CE-62-M	115 IN	Standard	End Stop	Clamp	42 lbs.
BR-CE-62-M	115 IN	Standard	End Stop	Rotation	42 lbs.
CC-CE-62-M	115 IN	Standard	Clamp	Clamp	57 lbs.
CR-CE-62-M	115 IN	Standard	Clamp	Rotation	69 lbs.
RR-CE-62-M	115 IN	Standard	Rotation	Rotation	84 lbs.

Notes:

- Crossbars are spaced at six feet for rotations and up to six feet for other features.
- Contact Prime Design customer service for application specific questions.
- Check the vehicle manufacturer's recommendation for roof capacity weight limits.
- A wide range of accessories are available including retractable ratchet tie downs, conduit carriers, lighting mounts, and more.

Van Crossbar Spacing and Ladder Size Guide

Crossbar Spacing	Step Ladder Size	Extension Ladder Size
5 ft spacing	8 – 10 ft.	16 – 24 ft.
6 ft spacing	8 – 12 ft.*	16 – 28 ft.

*12 ft. step ladders may require an extended upper add-on component